Zhichao Lu[®], *Student Member, IEEE*, Gautam Sreekumar[®], Erik Goodman[®], Wolfgang Banzhaf[®], Kalyanmoy Deb[®], *Fellow, IEEE*, and Vishnu Naresh Boddeti[®], *Member, IEEE*

Abstract—Neural architecture search (NAS) has emerged as a promising avenue for automatically designing task-specific neural networks. Existing NAS approaches require one complete search for each deployment specification of hardware or objective. This is a computationally impractical endeavor given the potentially large number of application scenarios. In this paper, we propose *Neural Architecture Transfer* (NAT) to overcome this limitation. NAT is designed to efficiently generate task-specific custom models that are competitive under multiple conflicting objectives. To realize this goal we learn task-specific supernets from which specialized subnets can be sampled without any additional training. The key to our approach is an integrated online transfer learning and many-objective evolutionary search procedure. A pre-trained supernet is iteratively adapted while simultaneously searching for task-specific subnets. We demonstrate the efficacy of NAT on 11 benchmark image classification tasks ranging from large-scale multi-class to small-scale fine-grained datasets. In all cases, including ImageNet, NATNets improve upon the state-of-the-art under mobile settings ($\leq 600M$ Multiply-Adds). Surprisingly, small-scale fine-grained datasets benefit the most from NAT. At the same time, the architecture search and transfer is orders of magnitude more efficient than existing NAS methods. Overall, experimental evaluation indicates that, across diverse image classification tasks and computational objectives, NAT is an appreciably more effective alternative to conventional transfer learning of fine-tuning weights of an existing network architecture learned on standard datasets. Code is available at https://github.com/human-analysis/neural-architecture-transfer

Index Terms—Convolutional neural networks, neural architecture search, AutoML, transfer learning, evolutionary algorithms

1 INTRODUCTION

T^{MAGE} classification is a fundamental task in computer vision, where given a dataset and, possibly, multiple objectives to optimize, one seeks to learn a model to classify images. Solutions to address this problem fall into two categories: (a) Sufficient Data: A custom convolutional neural network architecture is designed and its parameters are trained from scratch using variants of stochastic gradient descent, and (b) Insufficient Data: An existing architecture designed on a large scale dataset, such as ImageNet [1], along with its pre-trained weights (e.g., VGG [2], ResNet [3]), is fine-tuned for the task at hand. These two approaches have emerged as the mainstays of present day computer vision.

Success of the aforementioned approaches is primarily attributed to architectural advances in convolutional neural networks. Initial efforts at designing neural architectures relied on human ingenuity. Steady advances by skilled practitioners has resulted in designs, such as AlexNet [4], VGG [2], GoogLe-Net [5], ResNet [3], DenseNet [6] and many more, which have led to performance gains on the ImageNet Large Scale Visual Recognition Challenge [1]. In most other cases, a recent large scale study [7] has shown that, across many tasks, transfer learning by fine-tuning ImageNet pre-trained networks outperforms networks that are trained from scratch on the same data.

Moving beyond manually designed network architectures, Neural Architecture Search (NAS) [8] seeks to automate this process and find not only good architectures, but also their associated weights for a given image classification task. This goal has led to notable improvements in convolutional neural network architectures on standard image classification benchmarks, such as ImageNet, CIFAR-10 [9], CIFAR-100 [9] etc., in terms of predictive performance, computational complexity and model size. However, apart from transfer learning by finetuning the *weights*, current NAS approaches have failed to deliver new models for both *weights* and *topology* on custom non-standard datasets. The key barrier to realizing the full potential of NAS is the large data and computational requirements for employing existing NAS algorithms on new tasks.

In this paper, we introduce *Neural Architecture Transfer* (NAT) to breach this barrier. Given an image classification task, NAT obtains custom neural networks (both *topology* and *weights*), optimized for possibly many conflicting objectives, and does so without the steep computational burden of running NAS for each new task from scratch. A single run of NAT efficiently obtains multiple custom neural networks spanning the entire trade-off front of objectives.

Our solution builds upon the concept of a supernet [10] which comprises of many subnets. All subnets are trained simultaneously through weight sharing, and can be sampled very efficiently. This procedure decouples the network training and the search phases of NAS. A many-objective¹ search can then be employed on top of the supernet to find all

Zhichao Lu is with the Southern University of Science and Technology, Shenzhen, Guangdong 518055, China. E-mail: luzc@sustech.edu.cn.

Gautam Sreekumar, Erik Goodman, Wolfgang Banzhaf, Kalyanmoy Deb, and Vishnu Naresh Boddeti are with the Michigan State University, East Lansing, MI 48824 USA. E-mail: {sreekum1, goodman, banzhafw, kdeb, vishnu}@msu.edu.

Manuscript received 1 May 2020; revised 28 Oct. 2020; accepted 31 Dec. 2020. Date of publication 19 Jan. 2021; date of current version 4 Aug. 2021. (Corresponding author: Vishnu Naresh Boddeti.)

Recommended for acceptance by H. J. Escalante, J. Vanschoren, W.-W. Tu, Y. Yu, S. Escalera, N. Pillay, R. Qu, N. Houlsby, and T. Zhang. Digital Object Identifier no. 10.1109/TPAMI.2021.3052758

^{1.} Problems having more than three objectives are called many-objective problems [11].

^{0162-8828 © 2021} IEEE. Personal use is permitted, but republication/redistribution requires IEEE permission. See https://www.ieee.org/publications/rights/index.html for more information.



Fig. 1. Overview: Given a dataset and objectives to optimize, NAT designs custom architectures spanning the objective trade-off front. NAT comprises of two main components, supernet adaptation and evolutionary search, that are iteratively executed. NAT also uses an online accuracy predictor model to improve its computational efficiency.

network architectures that provide the best trade-off among the objectives. However, training such supernets for each task from scratch is very computationally and data intensive. The key idea of NAT is to leverage an existing supernet and efficiently transfer it into a task-specific supernet, whilst simultaneously searching for architectures that offer the best trade-off between the objectives of interest. Therefore, unlike standard supernet-based NAS, we combine supernet transfer learning with the search process. At the conclusion of this process, NAT returns (i) subnets that span the entire objective trade-off front, and (ii) a task-specific supernet. The latter can now be utilized for all future deployment-specific NAS, i.e., new and different hardware or objectives, without any additional training.

The core of NAT's efficiency lies in only adapting the subnets of the supernet that will lie on the efficient trade-off front of the new dataset, instead of all possible subnets. But, the structure of the corresponding subnets is unknown before adaptation. We resolve this "chicken-and-egg problem" by adopting an online procedure that alternates between the two primary stages of NAT: (a) *supernet adaptation* of subnets that are at the current trade-off front, and (b) *evolutionary search* for subnets that span the many-objective trade-off front. A pictorial overview of the entire NAT method is shown in Fig. 1.

In the *adaptation* stage, we first construct a layer-wise empirical distribution from the promising subnets returned by evolutionary search. Then, subnets sampled from this distribution are fine-tuned. In the *search* stage, to improve the efficiency of the search, we adopt a surrogate model to quickly predict the objectives of any sampled subnet without a full-blown and costly evaluation. Furthermore, the predictor model itself is also learned online from previously evaluated subnets. We alternate between these two stages until our computational budget² is exhausted. The key contributions of this paper are:

 We introduce *Neural Architecture Transfer* as a NASpowered alternative to fine-tuning based transfer learning. NAT is powered by a simple, yet highly effective online supernet fine-tuning and online accuracy predicting surrogate model.

2. We manually set the computational budget to a maximum of 1 day on a 8-GPU (NVIDIA 2080Ti) server. This is equivalent to the computational resources available to a small lab.

- We demonstrate the scalability and practicality of NAT on multiple datasets corresponding to different scenarios; large-scale multi-class (ImageNet [1], CINIC-10 [12]), medium-scale multi-class (CIFAR-10, CIFAR-100 [9]), small-scale multi-class (STL-10 [13]), large-scale fine-grained (Food-101 [14]), mediumscale fine-grained (Stanford Cars [15], FGVC Aircraft [16]) and small-scale fine-grained (DTD [17], Oxford-IIIT Pets [18], Oxford Flowers102 [19]) datasets.
- Under mobile settings (≤600M MAdds), NATNets lead to state-of-the-art performance across all these tasks. For instance, on ImageNet, NATNet achieves a Top-1 accuracy of 80.5 percent at 600M MAdds.
- We also demonstrate the utility of NAT in searching for a backbone for semantic segmentation, a dense prediction task. On Cityscapes [20], NAT matches the mIoU performance of Auto-DeepLab [21] while using 4× fewer MAdds.
- Finally we demonstrate the scalability and utility of NAT across many objectives and on dense image prediction. Optimizing accuracy, model size and one of MAdds, CPU or GPU latency, NATNets dominate MobileNetV3 [22] across all objectives. We also consider a 12 objective problem of finding a common architecture across eleven datasets while minimizing MAdds. The best trade-off NATNet dominates all models across these datasets under mobile settings.

2 RELATED WORK

Recent years have witnessed growing interests in neural architecture search. The promise of being able to automatically search for task-dependent network architectures is particularly appealing as deep neural networks are widely deployed in diverse applications and computational environments. Early methods [33], [34] made efforts to simultaneously evolve the topology of neural networks along with weights and hyperparameters. These methods perform competitively with handcrafted networks on simple control tasks with shallow fully connected networks. Recent efforts [35] primarily focus on designing deep convolutional neural network architectures.

The development of NAS largely happened in two phases. Starting from NASNet [8], the focus of the first wave of methods was primarily on improving the predictive accuracy of CNNs including Block-QNN [36], Hierarchical NAS [37], and

| Methods | Search Method | Performance Prediction | Weight Sharing | Multiple Objective | Dataset Searched |
|-------------------|---------------|---------------------------|-------------------|------------------------|--|
| NASNet [8] | RL | | | | C10 |
| PNAS [23] | SBMO | √ | | | C10 |
| DARTS [24] | gradient | | \checkmark | | C10 |
| LEMONADE [25] | EA | | \checkmark | \checkmark | C10, C100, ImageNet64 |
| ProxylessNAS [26] | RL / gradient | | \checkmark | \checkmark^{\dagger} | C10, ImageNet |
| MnasNet [27] | RL | | | \checkmark^{\dagger} | ImageNet |
| EfficientNet [28] | RL+scaling | | | | ImageNet |
| ChamNet [29] | EA | \checkmark | | \checkmark^{\dagger} | ImageNet |
| MobileNetV3 [22] | RL+expert | | | \checkmark^{\dagger} | ImageNet |
| SPOS NAS [30] | EA | | \checkmark | \checkmark^{\dagger} | ImageNet |
| OnceForAll [31] | EA | \checkmark | \checkmark | \checkmark^{\dagger} | ImageNet |
| FBNetV2 [32] | gradient | | \checkmark | \checkmark^{\dagger} | ImageNet |
| NAT (this paper) | EA+transfer | √ | \checkmark | \checkmark | ImageNet, C10, C100, CINIC-10, STL-10, Flowers102, Pets, DTD, Cars, Aircraft, Food-101 |

TABLE 1 Comparison of NAT and Existing NAS Methods

[†] indicates methods that scalarize multiple objectives into one composite objective or as an additional constraint, see text for details.

AmoebaNet [38], etc. These methods relied on Reinforcement Learning (RL) or Evolutionary Algorithm (EA) to search for an optimal modular structure that is repeatedly stacked together to form a network architecture. The search was typically carried out on relatively small-scale datasets (e.g., CIFAR-10/100 [9]), following which the best architectures were transferred to ImageNet for validation. A steady stream of improvements over state-of-the-art on numerous datasets were reported. The focus of the second wave of NAS methods was on improving the search efficiency.

A few methods have also been proposed to adapt NAS to other scenarios. These include meta-learning based approaches [39], [40] with application to few-shot learning tasks. XferNAS [41] and EAT-NAS [42] illustrate how architectures can be transferred between similar datasets or from smaller to larger datasets. Some approaches [43], [44] proposed RL-based NAS methods that search on multiple tasks during training and transfer the learned search strategy, as opposed to searched networks, to new tasks at inference. Next, we provide short overviews on methods that are closely related to the technical approach in this paper. Table 1 provides a comparative overview of NAT to existing NAS approaches.

Performance Prediction. Evaluating the performance of an architecture requires a computationally intensive process of iteratively optimizing model weights. To alleviate this computational burden, regression models have been learned to predict an architecture's performance without actually training it. Baker et al. [45] use a radial basis function to estimate the final accuracy of architectures from its accuracy in the first 25 percent of training iterations. PNAS [23] uses a multilayer perceptron (MLP) and a recurrent neural network to estimate the expected improvement in accuracy if the current modular structure (which is later stacked together to form a network) is expanded with a new branch. Conceptually, both of these methods seek to learn a prediction model that extrapolate (rather than interpolate), resulting in poor correlation in prediction. OnceForAll [31] also uses a MLP to predict accuracy from architecture encoding. However, the model is trained offline for the entire search space, thereby requiring a large number of samples for learning (16K samples -> 2 GPU-days for just constructing the surrogate model). Instead of using uniformly sampled architectures to train the prediction model to approximate the entire landscape, ChamNet [29] trains many architectures through full SGD and selects only 300 samples of high accuracy with diverse efficiency (Multiply-adds, Latency, Energy) to train a prediction model offline. In contrast, NAT learns a prediction model in an online fashion only on the samples at the current trade-off front as we explore the search space. Such an approach only needs to interpolate over a much smaller space of architectures constituting the current trade-off front. Consequently, this procedure significantly improves both the accuracy and the sample complexity of constructing the prediction model.

Weight Sharing. Approaches in this category involve training a supernet that contains all searchable architectures as its subnets. They can be broadly classified into two categories depending on whether the supernet training is coupled with architecture search or decoupled into a two-stage process. Approaches of the former kind [24], [26], [46] are computationally efficient but return sub-optimal models. Numerous studies [47], [48], [49] allude to weak correlation between performance at the search and final evaluation stages. Methods of the latter kind [10], [31], [50] use performance of subnets (obtained by sampling the trained supernet) as a metric to select architectures during search. However, training a supernet beforehand for each new task is computationally prohibitive. In this work, we take an integrated approach where we train a supernet on large-scale datasets (e.g., ImageNet) once and couple it with our architecture search to quickly adapt it to a new task. An elaborated discussion connecting our method to existing approaches is provided in the supplementary materials, which can be found on the Computer Society Digital Library at http://doi.ieeecomputersociety.org/10.1109/ TPAMI.2021.3052758.

Multi-Objective NAS. Methods that consider multiple objectives for designing hardware specific models have also been developed. The objectives are optimized either through (i) scalarization, or (ii) Pareto-based solutions. The former include, ProxylessNAS [26], MnasNet [27], ChamNet [29], MobileNetV3 [22], and FBNetV2 [32] which use a scalarized objective or an additional constraint to encourage high accuracy and penalize compute inefficiency at the same time, e.g., maximize $Acc * (Latency/Target)^{-0.07}$. Conceptually, the search of architectures is still guided by a single objective and only one architecture is obtained per search. Empirically, multiple runs with different weighting of the objectives are needed to find an architecture with the desired trade-off, or multiple architectures with different complexities. Methods in the latter category include [25], [51], [52], [53], [54] and aim to approximate the entire Pareto-efficient frontier simultaneously-i.e. multiple architectures with different complexities are obtained in a single run. These approaches rely on heuristics (e.g., EA) to efficiently navigate the search space allowing practitioners to visualize the trade-off between the objectives and to choose a suitable network *a posteriori* to the search. NAT falls into the latter category and uses an accuracy prediction model and weight sharing for efficient architecture transfer to new tasks.

3 PROPOSED APPROACH

Neural Architecture Transfer consists of three main components: an accuracy predictor, an evolutionary search routine, and a supernet. NAT starts with an archive A of architectures (subnets) created by uniform sampling from our search space. We evaluate the performance f_i of each subnet (a_i) using weights inherited from the supernet. The accuracy predictor is then constructed from (a_i, f_i) pairs which (jointly with any additional objectives provided by the user) drives the subsequent many-objective evolutionary search towards optimal architectures. Promising architectures at the conclusion of the evolutionary process are added to the archive A. The (partial) weights of the supernet corresponding to the top-ranked subnets in the archive are fine-tuned. NAT repeats this process for a pre-specified number of iterations. At the conclusion, we output both the archive and the task-specific supernet. Networks that offer the best trade-off among the objectives can be post-selected from the archive. Detailed descriptions of each component of NAT are provided in the following subsections. Fig. 1 and Algorithm 1 provide an overview of our entire approach.

| A | lgorithm 1: Neural Architecture Transfer | | | | | | |
|---------|--|-------------------------|--|--|--|--|--|
| | Input : Training data \mathcal{D}_{trn} , validation data \mathcal{D}_{vld} , additional objectives \tilde{f} , supernet \mathcal{S}_w , archive size N , # of iterations T . # of enochs E . # of generations G . | | | | | | |
| 1 | $t \leftarrow 0$ // initialize an iteration counter. | | | | | | |
| 2 | $\mathcal{A} \leftarrow$ randomly initialize an archive of archs with a | size of N . | | | | | |
| 3 | while $t < T$ do | C | | | | | |
| 4 | // compute accuracy by inheriting weights and i | nterence. | | | | | |
| 5 | $J \leftarrow \mathcal{S}_w(\mathcal{A}, \mathcal{D}_{vld})$ | | | | | | |
| 6 | f' construct the accuracy predictor. | 4 1 20 2 | | | | | |
| 7 | $\mathcal{S}_f \leftarrow Accuracy Fredicior(\mathcal{A}, f)$ | \triangleleft Algo. 2 | | | | | |
| 8 | \tilde{F} independent in a production of the second s | 4 Algo 2 | | | | | |
| 9 10 | $F_t \leftarrow Evolutionary Search(S_f, J, A, G)$ | ⊲ Aigo. 5 | | | | | |
| 10 | $A \neq Selection(A + B N)$ | 4 Algo 4 | | | | | |
| 11 | $\mathcal{A} \leftarrow Selection(\mathcal{A} \cup T_t, \mathcal{N})$ | ⊲ Aigo. 4 | | | | | |
| 12 | $S \neq Adapt(S = A D_{1} = F)$ | d Algo 5 | | | | | |
| 13 | $\mathcal{O}_w \leftarrow Addp(\mathcal{O}_w, \mathcal{A}, \mathcal{D}_{trn}, E)$ | ⊲ Aigo. 5 | | | | | |
| 14 | $ t \leftarrow t + 1$ | | | | | | |
| 16 | // optional in case of no preferences from users | | | | | | |
| 17 | 17 $\mathcal{A}^* \leftarrow$ choose a subset of archs from \mathcal{A} based on trade-offs by | | | | | | |
| ~ ′ | method presented in supplementary materials under Section 3. | | | | | | |
| 18 | Return $\mathcal{S}_w, \mathcal{A}, \mathcal{A}^*$. | | | | | | |

3.1 Problem Formulation

ŝ

The problem of neural architecture search for a target dataset $\mathcal{D} = {\mathcal{D}_{trn}, \mathcal{D}_{vld}, \mathcal{D}_{tst}}$ with many objectives can be formulated as the following bilevel optimization problem [55],

minimize
$$F(a) = (f_1(a; w^*(a)), \dots, f_m(a; w^*(a)))^T$$
,
subject to $w^*(a) \in \arg \min \mathcal{L}(w; a)$, (1)
 $a \in \mathbf{\Omega}_a, w \in \mathbf{\Omega}_w$,

where the upper-level variable *a* defines a candidate architecture, and the lower-level variable w(a) denotes its associated weights. $\mathcal{L}(w; a)$ is the cross-entropy loss on the training data \mathcal{D}_{trn} for an architecture *a*. $F : \Omega \to \mathbb{R}^m$ constitutes *m* (user-) desired, possibly competing, objectives—e.g., predictive performance on validation data \mathcal{D}_{vld} , number of parameters (#Params), multiply-adds (#MAdds), latency / power consumption / memory footprint on specific hardware etc.

The bi-level optimization is typically solved in an iterative fashion, with an inner optimization loop over the weights of the network for a given architecture, and an outer optimization loop over the network architectures themselves. The computational challenge of solving this problem stems from both the upper and lower level optimization. Learning optimal weights of a network in the lower level necessitates costly iterations of stochastic gradient descent over multiple epochs. Similarly, searching the optimal architecture on the upper level is prohibitive due to the discrete nature of the architecture description, size of search space and our desire to optimize many, possibly conflicting, objectives.

3.2 Search Space and Encoding

The search for optimal network architectures can be performed over many different search spaces. The generality of the chosen search space has a major influence on the quality of results that are feasible. We adopt a modular design for overall structure of the *network*, consisting of a stem, multiple stages and a tail (see Fig. 2a). The *stem* and *tail* are common to all networks and not searched. Each *stage* in turn comprises of multiple layers, and each *layer* itself is an inverted residual bottleneck structure [56].

-Network. We search for the input image resolution and the width multiplier (a factor that scales the # of output channels of each layer uniformly [57]). Following previous work [27], [28], [31], we segment the CNN architecture into five sequentially connected stages. The stages gradually reduce the feature map size and increase the number of channels (Fig. 2a *Left*).

-Stage: We search over the number of layers, where only the first layer uses stride 2 if the feature map size decreases, and we allow each block to have minimum of two and maximum of four layers (Fig. 2a *Middle*).

-*Layer:* We search over the expansion ratio (between the # of output and input channels) of the first 1×1 convolution and the kernel size of the depth-wise separable convolution (Fig. 2a *Right*).

Overall, we search over four primary hyperparameters of CNNs i.e., the depth (# of layers), the width (# of channels),





(b) Encoding

Fig. 2. The architectures in our search space are variants of Mobile-NetV2 family of models [22], [27], [28], [56]. (a) Each networks consists of five stages. Each stage has two to four layers. Each layer is an inverted residual bottleneck block. The search space includes, input image resolution (R), width multiplier (W), the number of layers in each stage, the # of output channels (expansion ratio E) of the first 1×1 convolution and the kernel size (K) of the depth-wise separable convolution in each layer. (b) Networks are represented as 22-integer strings, where the first two correspond to resolution and width multiplier, and the rest correspond to the layers. Each value indicates a choice, e.g., the third integer (L_1) takes a value of "1" corresponds to using expansion ratio of 3 and kernel size of 3 in layer 1 of stage 1.

the kernel size, and the input resolution. The resulting volume of our search space is approximately 3.5×10^{19} for each combination of image resolution and width multiplier.

To encode these architectural choices, we use an integer string of length 22, as shown in Fig. 2b. The first two values represent the input image resolution and width multiplier, respectively. The remaining 20 values denote the expansion ratio and kernel size settings for each of the 20 layers. The available options for expansion ratio and kernel size are [3, 4, 6] and [3, 5, 7], respectively. It is worth noting that we sort the layer settings in ascending #MAdds order, which is beneficial to the mutation operator used in our evolutionary search algorithm.

3.3 Accuracy Predictor

The main computational bottleneck of NAS arises from the nested nature of the bi-level optimization problem. The inner optimization requires the weights of the subnets to be thoroughly learned prior to evaluating its performance. Methods like weight-sharing [31], [46], [50] allow sampled subnets to inherit weights among themselves or from a supernet, avoiding the time-consuming process (typically



Fig. 3. *Top Path:* A typical process of evaluating an architecture in NAS algorithms. *Bottom Path:* Accuracy predictor aims to bypass the time-consuming components for evaluating a network's performance by directly regressing its accuracy f from a (architecture in the encoded space).

requiring hours) of learning weights through SGD. However, standalone weight-sharing still requires inference on validation data (typically requiring minutes) to assess performance. Therefore, simply having to evaluate the subnets can still render the overall process computationally prohibitive for methods [8], [27], [38] that sample thousands of architectures during search.

To mitigate the computational burden of fully evaluating the subnets, we adopt a surrogate accuracy predictor that regresses the performance of a sampled subnet without performing training or inference. By learning a functional relation between the integer-strings (subnets in the encoded space) and the corresponding performance, this approach decouples the evaluation of an architecture from data-processing (including both SGD and inference). Consequently, the evaluation time reduces from hours/minutes to seconds. We illustrate this concept in Fig. 3. The effectiveness of this idea, however, is critically dependent on the quality of the surrogate model. Below we identify three desired properties of such a model:

- Reliable prediction: high rank-order correlation³ between predicted and true performance.
- 2) Consistent prediction: the quality of the prediction should be consistent across different datasets.
- Sample efficiency: minimizing the number of training examples necessary to construct an accurate predictor model, since each training sample requires costly training and evaluation of a subnet.

Current approaches [23], [29], [31] that use surrogate based accuracy predictors, however, do not satisfy property (1) and (3) simultaneously. For instance, PNAS [23] uses 1,160 subnets to build the surrogate but only achieves a rank-order correlation of 0.476. Similarly, OnceForAll [31] uses 16,000 subnets to build the surrogate. The poor sample complexity and rank-order correlation of these approaches, is due to the offline learning of the surrogate model. Instead of focusing on models that are at the trade-off front of the objectives, these surrogate models are built for the entire search space. Consequently, these methods require a significantly larger and more complex surrogate model.

3. Low mean square error is also desirable, but not necessary since the selection of architectures in the subsequent evolutionary search compares relative performance between architectures.



Fig. 4. Accuracy predictor performance as a function of training samples. For each model, we show the mean and standard deviation of the Spearman rank correlation on 11 datasets (Table 3). The size of RBF ensemble is 500.

Algorithm 2. Accuracy Predictor (RBF Ensemble)

Input: Training data *X*, training targets *Y*, ensemble size *K*

- 1 $k \leftarrow 0 / /$ initialize an counter.
- 2 *pool* $\leftarrow \emptyset$ // initialize a pool to store all models.

3 while $k < K \operatorname{do}$

- 4 $(X, Y) \leftarrow$ randomly create a subset of the training data.
- 5 $idx \leftarrow$ randomly pick a subset of the features in training data.
- 6 $rbf \leftarrow \text{fit a RBF model from } X[:, idx] \text{ and } Y.$
- 7 $pool \leftarrow pool \cup (rbf, idx) / /$ append the fitted model to the pool.

8
$$k \leftarrow k + 1$$

9 end

10 **Return** a *pool* of *K* RBF models.

We overcome the aforementioned limitation by restricting the surrogate model to the search space that constitutes the current objective trade-off. Such a solution significantly reduces the sample complexity of the surrogate and increases the reliability of its predictions. We adopt four low-complexity predictors, namely, Gaussian Process (GP) [29], Radial Basis Function (RBF) [45], Multilayer Perceptron (MLP) [23], and Decision Tree (DT) [58]. Empirically, we observe that RBFs are consistently better than the other three models if the # of training samples is more than 100. To further improve RBF's performance, especially under a high sample efficiency regime, we construct an ensemble of RBF models. As outlined in Algorithm 2, each RBF model is constructed with a subset of samples and features randomly selected from the training instances. The correlation between predicted accuracy and true accuracy from an ensemble of 500 RBF models outperforms all other models across all regimes. Fig. 4 compares the performance of the different surrogate models we considered. Practically, we observed that the RBF ensemble can be learned under a minute.

3.4 Many-Objective Evolutionary Search

Given the accuracy predictor, we employ a customized evolutionary algorithm (EA) to search for optimal architectures that offer the best trade-off between many objectives. The EA is an iterative process in which initial architectures, selected from the archive of previously explored architectures, are gradually improved as a group, referred to as a *population*. In every generation (iteration), a group of *offspring* (i.e., new architectures) are created by applying variations through crossover and mutation (described below) operations on the most promising architectures, also known as *parents*, found so far in the population. Every member of the population, i.e., both parents and offspring, competes for survival and reproduction (becoming a parent) in each generation. See Fig. 1 (bottom right shaded in green) for a pictorial overview, and Algorithm 3 for the pseudocode.

Algorithm 3. Evolutionary Search

- **Input**: Accuracy predictor S_f , additional objectives \tilde{f} , archive of archs A, max. # of generations G, population size K, crossover probability p_{cr} mutation probability p_m .
- 1 $g \leftarrow 0 / /$ initialize an generation counter.
- 2 $f \leftarrow S_f(\mathcal{A}) / /$ compute accuracy of all archs in archive.
- 3 $P \leftarrow Selection(\mathcal{A}, f, \tilde{f}(\mathcal{A}), K) / /$ initialize the parent population with top-*K* ranked archs from \mathcal{A} .
- 4 while $g < G \operatorname{do}$
- 5 // choose parents through tournament selection for mating.
- 6 $P \leftarrow Binary Tournament Selection(P)$
- 7 // create offspring population by crossover between parents.
- 8 $Q \leftarrow Crossover(P, p_c)$
- 9 // induce randomness to offspring population through mutation.
- 10 $Q \leftarrow Mutation(Q, p_m)$
- 11 $R \leftarrow P \cup Q / /$ merge parent and offspring population.
- 12 // survive the top-*K* archs to next generation.
- 13 $P \leftarrow Selection(R, S_f(R), \tilde{f}(R), K)$
- $14 \quad g \leftarrow g+1$
- 15 **end**
- 16 **Return** parent population *P*.

Crossover exchanges information between two or more population members to create two or more new members. Designing an effective crossover between non-standard solution representations can be difficult and has been largely ignored by existing EA-based NAS algorithms [37], [38], [59]. Here we adopt a customized, homogeneous cross-over that uniformly picks integers from parent architectures to create offspring architectures. This crossover operator offers two properties: (1) it preserves common integers shared between parents; and (2) it is free of additional hyperparameters. Fig. 5a visualizes our implementation of the crossover operation. We generate two offspring architectures with each crossover, and an offspring population of the same size as the parent population is generated in each generation.

Mutation is a *local* operator that perturbs a solution to produce a new solution in its vicinity. In this work, we use a discretized version of the polynomial mutation (PM) operator [60] and apply it to every solution created by the cross-over operator. For a given architecture a, PM is carried out integer-wise with probability p_m , and the mutated *i*th integer, a_i , of the mutated offspring is:

$$a'_{i} = \begin{cases} a_{i} + ((2u)^{1/(1+\eta_{m})} - 1)(a_{i} - a_{i}^{(L)}), & \text{for } u \leq 0.5, \\ a_{i} + (1 - (2(1-u))^{1/(1+\eta_{m})})(a_{i}^{(U)} - a_{i}), & \text{for } u > 0.5, \end{cases}$$
(2)



Fig. 5. (a) *Crossover Operator*: new offspring architectures are created by recombining integers from two parent architectures. The probability of choosing from either one of the parents is equal. (b) *Mutation Operator*: histograms showing the probabilities of mutated values with current value at 5 under different hyperparameter η_m settings.

where u is a uniform random number in the interval [0, 1]. $a_i^{(L)}$ and $a_i^{(U)}$ are the lower and upper bounds of a_i , respectively. Each mutated value in an offspring is rounded to the nearest integer. The PM operator inherits the parent-centric convention, in which the offspring are intentionally created around the parents. The centricity is controlled via an index hyperparameter η_m . In particular, high-values of η_m tend to create mutated offspring around the parent, and low-values encourage mutated offspring to be further away from the parent architecture. See Fig. 5b for a visualization of the effect of η_m . It is the worth noting that the PM operator was originally proposed for continuous optimization where distances between variable values are naturally defined. In contrast, in context of our encoding, our variables are categorical in nature, indicating a particular layer hyperparameter. So we sort the searched subnets in ascending order of #MAdds, such that η_m now controls the difference in #MAdds between the parent and the mutated offspring.

We apply PM to every member in the offspring population (created from crossover). We then merge the mutated offspring population with the parent population and select the top half using many-objective selection operator described in Algorithm 4. This procedure creates the parent population for the next generation. We repeat this overall process for a pre-specified number of generations and output the parent population at the conclusion of the evolution.

3.5 Many-Objective Selection

In addition to high predictive accuracy, real-world applications demand NAS algorithms to simultaneously balance a few other conflicting objectives that are specific to the deployment scenarios. For instance, mobile or embedded devices often have restrictions in terms of model size, multiply-adds, latency, power consumption, and memory footprint. With no prior assumption on the correlation among these objectives, a scalable (to the number of objectives) selection is required to drive the search towards the high dimensional Pareto front. In this work, we adopt the reference point guided selection originally proposed in NSGA-III [11], which has been shown to be effective in handling problems with as many as 15 objectives. In the remainder of this section, we provide an overview of NSGA-III procedure and refer readers to the original publication for more details.

Algorithm 4. Reference Point Based Selection

Input: A set of archs *R*, their objectives *F*, number of archs to select *N*, reference directions *Z*.

- 1 // put archs into different fronts (rank levels) based on domination.
- 2 $(F_1, F_2, \ldots) \leftarrow non_dominated_sort(F)$
- 3 $S \leftarrow \emptyset, i \leftarrow 1$
- 4 while $|S| + |F_i| < N$ do $S \leftarrow S \cup F_i$; $i \leftarrow i + 1$
- 5 $F_L \leftarrow F_i$ // next front is the split front where we cannot accommodate all archs associated with it.
- 6 if $|S| + |F_L| = N$ then $S \leftarrow S \cup F_L$
- 7 else
- 8 $(\tilde{S}, \tilde{F}_L) \leftarrow Normalize(S, F_L) / / normalize the objectives based the ideal and nadir points derived from$ *R*.
- 9 $d \leftarrow$ compute orthogonal dist to Z_i for each i
- 10 $\rho \leftarrow \text{count #associated solutions for } Z_i \text{ based on } d \text{ for each } i.$
- 11 // remaining archs from F_L to fill up S.
- 12 $S \leftarrow S \cup Niching(\tilde{F}_L, N |S|, \rho, d)$
- 13 end
- 14 Return S.

Domination is a widely-used partial ordering concept for comparing two objective vectors. For a generic many-objective optimization problem: $\min_{a} \{f_1(a), \ldots, f_m(a)\}$, where $f_i(\cdot)$ are the objectives (say, loss functions) to be optimized and a is the representation of a neural network architecture. For two given solutions a_1 and a_2 , solution a_1 is said to dominate a_2 (i.e., $a_1 \leq a_2$) if following conditions are satisfied:

- 1) a_1 is no worse than a_2 for all objectives $(f_i(a_1) \le f_i(a_2), \forall i \in \{0, ..., m\})$, and
- 2) a_1 is strictly better than a_2 in at least one objective $\exists i \in \{0, ..., m\} | f_i(a_1) < f_i(a_2)).$

A solution a_i is said to be non-dominated if these conditions hold against all the other solutions a_j (with $j \neq i$) in the entire search space of a.

With the above definition, we can sort solutions to different ranks of domination, where solutions in the same rank are non-dominated to each other, and there exists at least one solution in lower rank that dominates any solution in the higher rank. Thus, a lower non-dominated ranked set is lexicographically better than a higher ranked set. This process is referred as non_dominated_sort, and it is the first step in the selection process. During the many-objective selection process, the lower ranked sets are chosen one at a time until no more sets can be included to maintain the population size. The final accepted set may have to be *split* to choose only a part. For this purpose, we choose the most diverse subset based on a diversity-maintaining mechanism. We first create a set of reference directions from a set of uniformly distributed (in (m-1)-dimensional space) reference points in the unit simplex by using Das-and-Dennis method [61]. Then we associate each solution to a reference direction based on orthogonal distance of the solution from the direction. Then, for every reference direction, we choose the closest associated solution in a systematic manner by adaptively computing a niche count ρ so that every reference direction gets an equal opportunity to choose a representative closest solution in the selected population. The domination and diversity-preserving procedures are easily scalable to any number of objectives and importantly are free



Fig. 6. (a) An example (assuming minimization of all objectives) of the selection process in Algo 4: We first create reference directions Z by joining reference points with the ideal solution (origin). Then through *non_dominated_sort*, three non-dominated solutions are identified, associated with reference directions $Z^{(1)}$, $Z^{(3)}$ and $Z^{(5)}$. We then select the remaining solutions by the orthogonal distances to the reference directions with no associated solutions—i.e. $Z^{(2)}$ and $Z^{(4)}$. This selection is scalable to larger # of objectives. A tri-objective example is shown in (b).

from any user-defined hyperparameter. See Algorithm 4 for the pseudocode and Fig. 6 for a graphical illustration. A more elaborated discussion on the necessity of the reference point based selection is provided in the supplementary materials, available online, under Section 2.

3.6 Supernet Adaptation

Instead of training every architectures sampled during search from scratch, NAS with weight sharing [24], [46] inherits weights from previously-trained networks or from a supernet. Directly inheriting the weights obviates the need to optimize the weights from scratch and speeds up the search from thousands of GPU days to only a few. In this work, we focus on the supernet approach [10], [31]. It involves first training a large network model (in which searchable architectures become subnets) prior to the search. Then the performance of the subnets, evaluated with the inherited weights, is used to guide the selection of architectures during search. The key to the success of this approach is that the performance of the subnets with the inherited weights be highly correlated with the performance of the same subnet when thoroughly trained from scratch. Satisfying this desideratum necessitates that the supernet weights be learned in such a way that all subnets are optimized simultaneously.

Algorithm 5. Adapt Supernet

Input: Supernet S_w, archive of archs A, training data D_{trn}, number of epochs E.
1 e ← 0 // initialize an epoch counter.
2 Distr ← construct the distribution from A following Eq. (3).
3 while e < E do
4 for each batch in D_{trn} do
5 subnet ← sample from Distr.

6 $w \leftarrow \text{set forward path of } S_w \text{ according to subnet.}$

9 $S_w \leftarrow$ one step of SGD.

- 10 end
- $11 \quad e \leftarrow e + 1$
- 12 end

13 **Return** supernet S_w .

Existing methods [30], [53] attempt to achieve the above goal by imposing *fairness* in training the supernet, where the probabilities of training any particular subnet for each batch of data is uniform in expectation. However, we argue that simultaneously training all the subnets in the search space is practically not feasible and, more importantly, not necessary. First, it is evident from existing NAS approaches [26], [62] that different objectives (#Params, #MAdds, latency on different hardware, etc.) require different architectures in order to be efficient. In other words, not all subnets are equally important for the task at hand. Second, only a tiny fraction⁴ of the search space can practically be explored by a NAS algorithms.

Based on the aforementioned observations, we propose a simple yet effective supernet training routine that only focuses on training the subnets recommended by the evolutionary search algorithm in Section 3.5. Specifically, we seek to exploit the knowledge gained from the search process so far. Recall that our algorithm uses an archive to keep track of the promising architectures explored so far. For each value in our architecture encoding, we construct a categorical distribution from architectures in the archive, where the probability for *i*th integer taking on the *j* value is computed as:

$$p(X_i = j) = \frac{\# \text{ of architectures with option } j \text{ at ith integer}}{\text{total } \# \text{ of architectures in the archive}}.$$
(3)

In each training step (batch of data), we sample an integerstring from the above distribution⁵. We then activate the sub parts of the supernet corresponding to the architecture decoded from the integer-string. Only weights corresponding to the activated sub parts in the supernet will be updated in each step. See Algorithm 5 for pseudocode. A more in-depth discussion connecting our proposed approach to the existing supernet-based NAS approaches is provided in the supplementary materials, available online, under Section 1.

4 EXPERIMENTAL EVALUATION

In this section, we present experimental results to evaluate the efficacy of *Neural Architecture Transfer* on multiple image classification tasks. In addition, we also investigate the scalability of our approach to more than two objectives. For all the experiments in this section, we use the same set of hyperparmaters (see Table 2) for the different components of NAT. These choices were guided by the ablation studies described in Section 5.

4.1 Datasets

We consider eleven image classification datasets for evaluation with sample size varying from 2,040 to 180,000 images (20 to 18,000 images per class; Table 3). These datasets span a wide variety of image classification tasks, including superordinate-level recognition (ImageNet [1], CIFAR-10 [9], CIFAR-100 [9], CINIC-10 [12], STL-10 [13]); fine-grained recognition (Food-101 [14], Stanford Cars [15], FGVC Aircraft

4. For example, AmoebaNet [38] samples a large number of 27K architectures which is still only about 10^{-13} percent of its search space.

5. A visualization of such distributions is shown in Fig. 3 of supplementary material, available online.

⁷ $\mathcal{L} \leftarrow$ compute cross-entropy loss on data *batch*.

⁸ $\nabla w \leftarrow \text{compute the gradient by } \partial \mathcal{L} / \partial w$

TABLE 2 Hyperparameter Settings

| Category | Parameter | Setting |
|---------------------|--|---------------------------------|
| Global | Archive size Number of iterations | 300 30 |
| Accuracy predictor | Train size Ensemble size | 100 500 |
| Evolutionary search | Population size Number of generations per iteration Crossover probability Mutation probability Mutation index η_m | 100 100 0.9 0.1 1.0 |
| Supernet | Number of epochs per iteration | 5 |

[16], Oxford-IIIT Pets [18], Oxford Flowers102 [19]); and texture classification (DTD [17]). We use the ImageNet dataset for training the supernet, and use the other ten datasets for architecture transfer.

4.2 Supernet Preparation

Our supernet is constructed by setting the architecture encoding at the maximum value, i.e. four layers in each stage and every layer uses expand ratio of six and kernel size of seven. Adapting subnets of a supernet with randomly initialized weights leads to training instability and large variance in its performance. Therefore, we warm-up the supernet weights on ImageNet following the progressive shrinking algorithm [31], where the supernet is first trained at full-scale, with subnets corresponding to different options (expand ratio, kernel size, # of layers) being gradually activated during the training process. This procedure, which takes about 6 days on a server with eight V100 GPUs, is optimized with only the cross-entropy loss i.e., a single objective. We note that supernet preparation expense is a one-time cost that amortizes over any subsequent transfer to different datasets and objective combinations we show in the following subsections.

4.3 ImageNet Classification

Before we evaluate our approach for architecture transfer to other datasets, we first validate its effectiveness on the ImageNet-1K dataset. This experiment evaluates the effectiveness of NAT in adapting and searching for architectures that span trade-off between two objectives. For this experiment, we consider accuracy and #MAdds as the two objective of interest. We randomly sample 50,000 images from the original ImageNet training set as the validation set to guide the architecture search. We run NAT for 30 iterations, and from the final archive of architectures, we select four models ranging from 200M MAdds to 600M MAdds (for high-end mobile devices). Following [31], we fine-tune⁶ each model to further boost the performance. Our fine-tune training largely follows [27]: RMSProp optimizer with decay 0.9 and momentum 0.9; batch normalization momentum 0.99; weight decay 1e-5. We use a batch size of 512 and

TABLE 3 Benchmark Datasets for Evaluation

| Dataset | Туре | Train Size | Test Size | #Classes |
|--|--------------|---|---|--------------------------------------|
| ImageNet [1] CINIC-10 [12] CIFAR-10 [9] CIFAR-100 [9] STL-10 [13] | multi-class | $1,281,167 \\180,000 \\50,000 \\50,000 \\5,000 \\5,000$ | 50,000 9,000 10,000 10,000 8,000 | 1,000 10 10 10 10 |
| Food-101 [14] Stanford Cars [15] FGVC Aircraft [16] DTD [17] Oxford-IIIT Pets [18] Oxford Flowers102 [19] | fine-grained | 75,750 8,144 6,667 3,760 3,680 2,040 | 25,250 8,041 3,333 1,880 3,369 6,149 | 101 196 100 47 37 102 |

an initial learning rate of 0.012 that gradually reduces to zero following the cosine annealing schedule. Our regularization settings are similar as in [28]: we use augmentation policy [63], drop connect ratio 0.2, and dropout ratio 0.2.

Table 4 shows the performance of NAT models obtained through bi-objective optimization of maximizing accuracy and minimizing #MAdds. Our models, referred to as NAT-M{1,2,3,4}, are in ascending order of #MAdds (Fig. 7). Fig. 8 shows the full #MAdds-accuracy trade-off curve comparison between NAT and existing NAS methods.

Results indicate that NATNets completely dominate (i.e. better in both #MAdds and accuracy) all existing designs, both manual and from other NAS algorithms, under mobile settings (≤600M MAdds). Compared to manually. designed networks, NAT is noticeably more efficient. NAT-M1 is 2.3 percent and 1.5 percent more accurate than MobileNetV3 [22] and FBNetV2-F4 [32] respectively, while being equivalent in efficiency (i.e. #MAdds, CPU and GPU latency). Furthermore, NATNets are consistently 6 percent more accurate than MobileNetV2 [56] scaled by width multiplier from 200M to 600M #MAdds. Our largest model, NAT-M4, achieves a new state-of-the-art ImageNet top-1 accuracy of 80.5 percent under mobile settings (≤600M #MAdds). Interestingly, even though this experiment did not explicitly optimize for CPU or GPU latency, NATNets are faster than those (MobileNet-V3 [22], MNasNet [27]) that explicitly do optimize for latency.

4.4 Scalability to Datasets

Existing NAS approaches are rarely applied to datasets beyond standard ones (i.e. CIFAR-10 [9] and ImageNet [1]), where the classification task is at superordinate-level and the # of training images are sufficiently large. Instead, they adopt a conventional transfer learning setup [7], in which the architectures found by searching on standard benchmark datasets are transferred as is, with weights fine-tuned to new datasets. We argue that such a process is conceptually contradictory to the goal of NAS. The architectures transferred from standard datasets are sub-optimal either with respect to accuracy, efficiency or both. On the other hand, by transferring both architecture and weights NAT can indeed design bespoke models for each dataset.

We evaluated NAT on ten image classification datasets (see Table 3) that present different challenges in terms of diversity in classes (superordinate versus fine-grained) and size of training set (large versus small). For each dataset, we run NAT with two objectives: maximize top-1 accuracy on

^{6.} Section 5.5 studies the impact of this fine-tuning step.

| Model | Method | #Params | #Multi-Adds | CPU Lat (ms) | GPU Lat (ms) | Top-1 Acc (%) | Top-5 Acc (%) |
|---|--|--|--|---|---|--|---|
| NAT-M1 MobileNetV2 [56] SPOS NAS [30] ProxylessNAS [26] MnasNet-A1 [27] MobileNetV3 [22] MUXNet-m [54] FBNetV2-F4 [32] | WS+EA manual WS+EA RL/gradient RL RL/NetAdapt EA gradient | 6.0M 3.5M 3.4M 4.0M 3.9M 5.4M 3.4M 7.0M | 225M 300M 328M 465M 312M 219M 218M 238M | 9.1 8.3 - 8.5 9.3 10.6 14.7 15.6 | 30 23 - 27 31 33 42 44 | 77.5 72.0 74.7 75.1 75.2 75.2 75.3 76.0 | 93.5 91.0 92.0 92.5 92.5 92.5 |
| NAT-M2 MUXNet-1 [54] EfficientNet-B0 [28] AtomNAS-C+ [64] AutoNL-L [65] DNA-c [66] | WS+EA EA RL/scaling WS+shrinkage gradient gradient | 7.7M 4.0M 5.3M 5.9M 5.6M 5.3M | 312M 318M 390M 363M 353M 466M | <u>11.4</u> 19.2 14.4 - 14.5 | 37 74 46 - 67 | 78.6 76.6 77.1 77.6 77.7 77.8 | 94.3 93.2 93.2 93.5 93.7 93.7 |
| NAT-M3 ResNet-152 [3] MixNet-L [67] EfficientNet-B1 [28] | WS+EA manual RL RL/scaling | 9.1M 60M 7.3M 7.8M | 490M 11.3B 565M 700M | <u>16.1</u> 66.7 29.4 19.5 | <u>62</u> 176 105 67 | 79.9 77.8 78.9 79.1 | 94.9 93.8 94.2 94.4 |
| NAT-M4 BigNASModel-L [68] OnceForAll [31] Inception-v4 [69] Inception-ResNet-v2 [69] | WS+EA WS WS+EA manual manual | 9.1M 6.4M 9.1M 48M 56M | 0.6B 0.6B 13B 13B | 17.3 16.5 84.6 99.1 | 78 - 206 289 | 80.5 79.5 80.0 80.0 80.1 | 95.2 94.9 95.0 95.1 |

TABLE 4 ImageNet-1K Classification [1]: NATNets Comparison With Manual and Automated Design of Efficient Convolutional Neural Networks

validation data (20 percent randomly separated from the training set) and minimize #MAdds. We start from the supernet trained on ImageNet (which is created once before all experiments; see Section 4.2) and adapt it to the new dataset. During this procedure, the last linear layer is reset depending on the number of categories in the new dataset. NAT is now applied for a total of 30 iterations. In each iteration the supernet is adapted for 5 epochs using SGD with a momentum of 0.9. The learning rate is initialized at 0.01 and annealed to zero in 150 epochs (30 iterations with five epochs in each). All hyperparameters are set at default



values from Table 2. For each dataset, the overall NAT process takes slightly under a day on a server with eight 2080Ti GPUs.

Fig. 9 shows the accuracy and #MAdds trade-off for each dataset across a wide range of models, including NATNets, existing NAS and hand-designed models. Across all datasets, NATNets consistently achieve better accuracy while being an order of magnitude more efficient (#MAdds) than existing models, suggesting that searching directly on the targeted datasets is a more effective alternative to the conventional transfer learning that fine-tunes weights of architectures learned on standard datasets (i.e. ImageNet and CIFAR-10). Under mobile settings (<600M), NATNets achieve the stateof-the-art on these datasets, and a new state-of-the-art accuracy on both STL-10 [13] and CINIC-10⁷ [12] datasets. Surprisingly, on small scale datasets e.g., Oxford Flowers102 [19], Oxford-IIIT Pets [18], DTD [17] and STL-10 [13], we observe that NAT-Nets are significantly more effective than conventional finetuning. Even on fine-grained datasets such as Stanford Cars and FGVC aircraft, where conventional fine-tuning did not improve upon training from scratch, NATNets improve accuracy while also being significantly more efficient.

Fig. 10 shows a visualization of architectures with 350M MAdds for each dataset. The lack of similarity in the networks suggest that different datasets require different architectures to be efficient in *accuracy-MAdds*, and NAT is able to generate these customized networks for each dataset.

Fig. 7. ImageNet Architectures from Trade-Off Front.

7. According to [70] for STL-10, and [71] for CINIC-10.

Models are grouped into sections for better visualization. Our results are underlined and the best result in each section is in bold. CPU latency (batchsize=1) is measured on Intel i7-8700K and GPU latency (batchsize=64) is measured on 1080Ti. "WS" stands for weight sharing. All methods are under single crop and single model condition, without any additional data.

Authorized licensed use limited to: Michigan State University. Downloaded on August 06,2021 at 13:21:38 UTC from IEEE Xplore. Restrictions apply.



Fig. 8. *MAdds versus ImageNet Accuracy*. NATNets outperform other models in both objectives. In particular, NAT-M4 achieves a new state-of-the-art top-1 accuracy of 80.5 percent under mobile setting (≤600M MAdds). NAT-M1 improves MobileNetV3 top-1 accuracy by 2.3 percent with similar #MAdds.

Additional visualization of architectures searched on all datasets is provided in supplementary materials, available online, under Section 3.

4.5 Scalability to Objectives

Practical applications of NAS can rarely be considered from the point of view of a single objective, and most often, they must be evaluated from many different, possibly competing, objectives. We demonstrate the scalability of NAT to more than two objectives, and evaluate its effectiveness.

We use NAT to simultaneously optimize for three objectives—namely, model accuracy on ImageNet, model size (#params), and model computational efficiency. We consider three different metrics to quantify computational efficiency—#MAdds, CPU latency, and GPU latency. In total, we run three instances of three-objective search—i.e. maximize accuracy, minimize #params, and minimize one of #MAdds, CPU latency or GPU latency. We follow the settings from the ImageNet experiment in Section 4.3, except the fine-tuning step.

After obtaining the non-dominated (trade-off) solutions, we first visualize the objectives in Fig. 11. We observe that Pareto surfaces emerge at higher model complexity regime (i.e. high #params, #MAdds, etc.), shown in the 3D scatter plot in the top row, suggesting that trade-offs exist between model size (#params) and model efficiency (#MAdds and latency). In other words, #params and {#MAdds, CPU, GPU latency} are not completely correlated—e.g., a model with a fewer #params is not necessarily more efficient in #MAdds or latency than another model with more #params. This is one of the advantages of using a many-objective optimization algorithm compared to optimizing a single scalarized objective (such, as a weighted-sum of objectives [26], [27]).

Fig. 11 visualizes, in 2D, the top-1 accuracy as a trade-off with each one of the four considered efficiency metrics in the bottom row. The 2D projection is obtained by ignoring the third objective. For better visualization we only show the architectures that are close to the performance trade-off of MobilNetV3 [22]. NATNets obtained directly from the three-objective search i.e., before any fine-tuning of their weights, consistently outperform MobileNetV3 on ImageNet along all the objectives (top-1 accuracy, #params, #MAdds, CPU and GPU latency). Additionally, we compare to MUXNets [54] which are also obtained from a threeobjective NAS optimizing {top-1 accuracy, #params, and #MAdds}. However, MUXNets adopt a search space that is



Fig. 9. *MAdds versus Accuracy* trade-off curves comparing NAT and existing architectures on a diverse set of datasets. The datasets are arranged in ascending order of training set size. Methods shown in the legend pre-train on ImageNet and fine-tune the weights on the target dataset. Methods with names annotated in sub-figures train from scratch or use external training data.

Authorized licensed use limited to: Michigan State University. Downloaded on August 06,2021 at 13:21:38 UTC from IEEE Xplore. Restrictions apply.



Fig. 10. Efficient architectures (350M MAdds) obtained by NAT on ten diverse image classification datasets.

specifically tailored for reducing model size. Therefore, in comparison to MUXNets, we observe that NATNets perform favourably on all the remaining three efficiency metrics, except for #params. Primarily driven by curiosity in terms of pushing the scalability of our approach with respect to number of objectives, we provide an application to 12 objective problem in the supplementary materials, available online, under Section 6.

4.6 Utility on Dense Image Prediction

Dense image prediction is another series of important computer vision tasks, that assigns a label to each pixel in the input image [72], [73]. Success in these tasks relies on both feature extraction via a backbone CNN, e.g., ResNet [3], and feature aggregation, e.g., FPN [74], at multiple scales. In this section, we use NAT to design efficient backbone feature extractors for semantic segmentation, to demonstrate its utility beyond image classification.

Similar to previous studies, we start from the supernet trained on ImageNet (which is created once before all experiments; see Section 4.2). We remove the last classification layer and pair it with the BiSeNet segmentation heads [75], a lightweight semantic segmentation framework for real-time performance. We modify the searched input resolutions from [192, ..., 256] to [512, ..., 1280] and keep other searched options the same as before. NAT is applied to minimize #MAdds and maximize mIoU on validation data (20 percent randomly sampled from the training set) for 20 iterations. In each iteration, the supernet is adapted for 2K iterations using SGD with a momentum of 0.9 and weight decay of 5×10^{-4} . We use a batch size of eight for each GPU. We use an initial learning rate of 0.01 and follow the "poly" learning rate schedule from the original BiSeNet [75], in



Fig. 11. *Top row*: NATNets obtained from tri-objective search to maximize ImageNet top-1 accuracy, minimize model size (#Params), and minimize {#MAdds, CPU latency, GPU latency} from left to right. Pareto surfaces emerge at higher model complexity regime (i.e. top right corner) suggesting that trade-offs exist between model size (#params) and model efficiency (#MAdds and latency). *Bottom row*: 2D projections from above 3D scatter, showing top-1 accuracy versus each of the four efficiency related measurements. The first two 2D projections are from the first 3D scatter, and the remaining two 2D projections are from the second and third 3D scatters, respectively. To better visualize (the comparison with MobileNetV3 [22] and MUXNet [54]), partial solutions from the non-dominated frontiers are shown. All top-1 accuracy shown are without fine-tuning.

Authorized licensed use limited to: Michigan State University. Downloaded on August 06,2021 at 13:21:38 UTC from IEEE Xplore. Restrictions apply.



Fig. 12. *MAdds versus Cityscapes mIoU*. NAT obtained backbone feature extractors (green curve) significantly outperform the original BiSe-Net, which are based on ResNets (R18 - R152). With further fine-tuning of 4K iterations, NAT achieves the state-of-the-art performance (red curve).

TABLE 5 Cityscapes Semantic Segmentation [20]: All Results are Based on Single-Scale Inputs From Validation Set

| Method | #Params | #Multi-Adds | mIoU (%) |
|----------------------|---------|-------------|----------|
| BiSeNet [75] | 13.4M | 67B | 74.8 |
| PSPNet [76] | 65.9M | 2,017B | 78.4 |
| DeepLabv3+ [77] | 43.5M | 1,551B | 79.6 |
| Auto-DeepLab-S [21] | 10.2M | 333B | 79.7 |
| NAT + BiSeNet (ours) | 8.8M | 73B | 79.7 |

which the initial learning rate is multiplied by $(1 - \frac{iter}{max_iter})^{0.9}$ in each iteration. All other hyperparameters are set at default values from Table 2. On the Cityscapes dataset [20], the overall NAT process takes a day on a server with six Titan RTX GPUs.

Fig. 12 compares the *mIoU-MAdds* trade-off obtained by NAT and the original BiSeNet [75] on the Cityscapes dataset. Empirically, we observe that NAT based backbones consistently outperform the original BiSeNets, which are based on ResNets. To realize the full potential of the searched NAT-Nets, we further fine-tune the obtained models for 4K iterations. As shown in Table 5, the resulting NAT model yields comparable performance against state-of-the-art methods,

including PSPNet [76], DeepLabv3 [77], Auto-DeepLab-S [21], while being *4x* - 28*x* more efficient in #Madds.

5 ABLATION STUDY

In this section, we provide additional experiments towards quantifying the impacts of the main components introduced in NAT and hyperparameter analysis.

5.1 Accuracy Predictor Performance

In this subsection, we assess the effectiveness of different accuracy predictor models. We first uniformly sampled 350 architectures from our search space and trained them using SGD for 150 epochs on ImageNet. Each one of them is fine-tuned for 50 epochs on the other ten datasets (Table 3). From the 350 pairs of architectures and top-1 accuracy computed on each dataset, we reserved a subset (randomly chosen) of 50 pairs for testing, and the remaining 300 pairs are then available for training the predictor models.

Fig. 4 compares the mean (over 11 datasets) Spearman rank correlation between the predicted and the true accuracy for each accuracy predictor as the training sample size is varied from 50 to 300. Empirically, we observe that radial basis function (RBF) has higher Spearman rank correlation compared to the other three models. The proposed RBF ensemble model further improves performance over the standalone RBF model across all training sample size regimes. Fig. 13 shows a visualization of the comparative performance of predictor models on different datasets. From the trade-off perspective of minimizing number of training examples (which reduces the overall computational cost) and maximizing Spearman rank correlation in prediction (which improves the accuracy in ranking architectures during search), we chose the RBF ensemble as our accuracy predictor model and a training size of 100 for all our experiments.

5.2 Search Efficiency

The overall computation cost consumed by a NAS algorithm can be factored into three phases: (1) *Prior-search*: Cost incurred prior to architecture search, e.g., training supernet in case of one-shot approaches [10], [31] or constructing accuracy predictor [29], etc; (2) *During-search*: Cost associated with measuring the performance of candidate architectures sampled during



Fig. 13. *Top row:* Spearman rank correlation between predicted accuracy and true accuracy of different surrogate models across many datasets. Each accuracy predictor is constructed from 250 samples (trained architectures). Error bars show mean and standard deviation over ten runs. *Bottom row:* Goodness of fit visualization of RBF ensemble, the best accuracy predictor.

Authorized licensed use limited to: Michigan State University. Downloaded on August 06,2021 at 13:21:38 UTC from IEEE Xplore. Restrictions apply.

| | Method | Type | Top-1 Acc. (%) | #MAdds (M) | Estimated Search Cost (GPU hours) | | | |
|----------|-----------------|-------------|----------------|------------|-----------------------------------|---------------------|-------------|-----------------|
| | | | 1 | (,,,, | Prior-search | During-search | Post-search | Total |
| ImageNet | MnasNet [27] | gradient | 75.2 | 312 | - | - | - | $91k^{\dagger}$ |
| 0 | OnceForAll [31] | WS+EA | 76.9 | 230 | 1,200 | 40 | 75 | 1.3k |
| | NAT (ours) | WS+EA | 77.5 | 225 | 1,200 | 150 | 75 | 1.4k |
| CIFAR-10 | NASNet [8] | RL | 97.4 | 569 | - | 10,000 [‡] | 6000* | 16k |
| | PNASNet [23] | SMBO | 96.6 | 588 | - | 600 [‡] | 36 | 0.6k |
| | DARTS [24] | WS+gradient | 97.3 | 595 | - | 96 | 36 | 0.1k |
| | AmoebaNet [38] | ĔA | 97.5 | 555 | - | 13,500 [‡] | 2400* | 16k |
| | NAT (ours) | transfer+EA | 98.4 | 468 | - | 150 | - | 0.1k |

TABLE 6 Comparing the Relative Search Efficiency of NAT to Other Methods

"-" denotes for not applicable, "WS" stands for weight sharing and "SMBO" stands for sequential model-based optimization [79].

 † is taken from [32], ‡ estimate based on the # of models evaluated during search (20K in [8], 1.2K in [23], 27K in [38]).

* denotes re-ranking stage where top 100-250 models undergo extended training and evaluation for 300 epochs before selecting the final model.

search through inference. It also includes the cost of training the supernet in case it is coupled with the search, like in [24] and NAT; (3) Post-search: Cost associated with choosing a final architecture, and/or fine-tuning/re-training the final architectures from scratch. For comparison, we select representative NAS algorithms, including those based on reinforcement learning (RL), gradients, evolutionary algorithm (EA), and weight sharing (WS). Table 6 shows results for ImageNet and CIFAR-10. The former is the dataset on which the supernet is trained and the latter is a proxy for transfer learning to a nonstandard dataset. NAT consistently achieves better performance, both in terms of top-1 accuracy and model efficiency (e.g., #MAdds), compared to the baselines while computational cost is similar or lower. The primary computational cost of NAT is the prior-search training of supernet for 1200 hours. We emphasize, again, that it is a one-time cost that is amortized across all subsequent deployment scenarios (e.g., 10 additional datasets in Section 4.4).

Comparing the search phase contribution to the success of different NAS algorithms is challenging and ambiguous due to substantial disparities in search spaces and training procedures. So, we conduct the following controlled experiment where we replace only the evolutionary search component in the NAT pipeline with (1) a random search that uniformly samples (with possible repetition) from the search space, and (2) NSGANet [51], another multi-objective EA-based NAS algorithm. This experiment is under a biobjective setup: maximize top-1 accuracy and minimize #MAdds. We run each method five times on three datasets to capture the variance in performance due to inherent stochasticity in the optimization initialization. We use hypervolume [78], a widely-used metric for comparing algorithms under multiple objectives, as the evaluation metric. Fig. 14 shows the mean and the standard deviation of the hypervolume achieved by each method. The evolutionary search component in NAT is $3 \times - 5 \times$ more sample efficient than the baselines for the same hypervolume.

5.3 Analysis of Crossover

Crossover is a standard operator in evolutionary algorithms, but has largely been avoided by existing EA-based NAS methods [37], [38], [59]. But as we demonstrate here, a carefully designed crossover operation can significantly improve search efficiency. We run the evolutionary search of NAT with and without the crossover operator on four datasets; ImageNet [1], CIFAR-10 [9], Oxford Flowers102 [19], and Stanford Cars [15]. The hyperparameters that we compare are:

- 1) *w*/ *crx*: crossover probability of 0.9; mutation probability of 0.1; mutation index η_m of 3.
- 2) *w*/*o crx*: crossover probability of 0.0; mutation probability of 0.2; mutation index η_m of 3.

We double the mutation probability when crossover is not used to compensate for the reduced exploration ability of the search. On each dataset, we run each setting to maximize the top-1 accuracy 11 times and report the median performance as a function of the number of architecture sampled in Fig. 15a. On all four datasets, the crossover operator significantly improves the efficiency of the evolutionary



Fig. 14. *Top left:* A sketch visualizing the hypervolume metric [78]. In case of bi-objective, it measures the dominated area achieved by a multi-objective algorithm. A larger hypervolume indicates a better Pareto front achieved. *Rest:* Search efficiency comparison between NAT, NSGANet [51], and random search under a bi-objective setup. Mean hypervolume over five runs are plotted with shaded region showing the standard deviation.



(b) Effect of Crossover Probability

Fig. 15. Ablation study on the crossover operator. (a) The median performance from eleven runs of our evolutionary algorithm with and without the crossover operator. (b) The median performance deteriorates as the crossover probability reduces from 0.9 to 0.2.

search algorithm. To further validate, we sweep over the probability of crossover while maintaining the rest of the settings. The median performance (over 11 runs) deteriorates as the crossover probability is reduced from 0.9 to 0.2 (see Fig. 15b).

5.4 Analysis of Mutation Hyperparameters

The mutation operator used in NAT is controlled via two hyperparameters—namely, the mutation probability p_m and mutation index η_m . To identify the optimal hyperparameter values, we conduct the following parameter sweep experiments. Setting the rest of the hyperparameters to their default values (see Table 2), we sweep the value of p_m from 0.1 to 0.8, and η_m from 1.0 to 20. And for each setting, we run NAT eleven times on four datasets (same as the crossover experiment) to maximize the top-1 accuracy. Figs. 16a and 16b show the effect of mutation probability p_m and mutation index η_m , respectively. We observe that increasing the mutation probability has an adverse effect on performance. Similarly, low values of η_m , which encourages the mutated offspring to be further away from parent architectures, improves the performance. Based on these observations, we set the mutation probability p_m and mutation index η_m parameters to 0.1 and 1.0, respectively, for all our experiments in Section 4.

5.5 Effectiveness of Supernet Adaptation

Recall that NAT adopts any supernet trained on a largescale dataset, e.g., ImageNet, and seeks to efficiently transfer to a task-specific supernet on a given dataset. Here, we compare this procedure to a more conventional approach of adapting every subnet (candidate architectures in search) directly. Specifically, we consider the following,

1) *Supernet Adaptation*: fine-tune supernet for 5 epochs in each iteration and use accuracy from inherited weights (without further training) to select architectures during search (adopted in NAT).



(b) Effect of Mutation Hyperparameter η_m

Fig. 16. Hyperparameter study on (a) mutation probability p_m and (b) mutation index parameter η_m . For each study, we run NAT eleven times on four datasets to maximize top-1 accuracy and report the median performance.



Fig. 17. Comparing the performance of *adapting supernet*, *adapting subnet* and *additional fine-tuning* under a bi-objective search setup on four datasets. Details are provided in Section 5.5.

2) *Subnet Adaptation:* fine-tune each subnet for 5 epochs from the inherited weights, then measure the accuracy.

We apply these two approaches to a bi-objective search of maximizing top-1 accuracy and minimizing #MAdds on four datasets, including CIFAR-10, CIFAR-100, Oxford Flowers102, and STL-10. Fig. 17 compares the final Pareto fronts. Adapting the supernet yields significantly better performance than adapting individual subnets. Furthermore, we select a subset of searched subnets after subnet adaptation and fine-tune their weights for an additional 150 epochs. We refer to this as additional fine-tuning in Fig. 17. Empirically, we observe that further fine-tuning can match the performance of supernet adaptation on datasets with larger training samples per class (e.g., 4,000 in CIFAR-10). On datasets with fewer samples per class (e.g., 20 in Flowers 102), there is still a large performance gap between supernet adaptation and additional fine-tuning. Overall the results suggest that supernet adaptation is more effective on tasks with limited training samples.

5.6 Towards Quantifying Architectural Advancement

Comparing the architectural contribution to the success of different NAS algorithms can be difficult and ambiguous due to substantial differences in training procedures, e.g., data augmentation, training hyperparameters, etc. Therefore, to quantify the architectural advancement made by NAT alone, we train NAT-M1 from randomly initialized weights (instead of inheriting them from the supernet) with standard training hyperparameters (see Table 7). We then compare the outcome to two other recently proposed efficient models, MobileNetV3 [22] and FBNetV2 [32]. The results are summarized in Table 8, where we observe that the NAT searched model, NAT-M1, is 0.5 - 1.0 percent more accurate on ImageNet than compared models using similar or less #MAdds.

To further quantify the architectural advancement made by NAT, we use NAT-M1 as a drop-in replacement of the backbone feature extractor for three dense image

TABLE 7 Details of Training Hyperparameter Settings

| Setting | Data Augmentation | Regularization | Optimizer | LR Schedule |
|-----------|---|------------------|---|---|
| Standard | Horizontal Flop + Crop | Drop out | | |
| Advance + | Random Augmentation [81] + Random Erase Pixel [82] | + Drop path [83] | RMSProp + Exponential Moving Averaging | Step LR w/ Decay + Linear Warm-up [80] |

Advance settings are in addition to standard settings.

prediction tasks, including object detection, semantic segmentation, and instance segmentation. More specifically, we replace the EfficientNet-B0 [28] in EfficientDet-D0 [84] for object detection; the ResNet-18 [3] in BiSeNet [75] for semantic segmentation; and the ResNet-50 [3] in YOLACT [85] for instance segmentation. For comparison, we apply the same procedure to both MobileNetV3 and FBNetV2 as well. The results are reported in Table 8. In general, our NAT searched model, NAT-M1, is consistently better than peer competitors across all tasks and datasets using similar or less #MAdds. Specifically, NAT-M1 is better than the compared models on all three datasets for semantic segmentation, achieving 1.0 - 2.3 higher mIoU.

Finally, we break down the effect of different training settings and additional fine-tuning for the Top-1 accuracy of the searched models in Table 9. The advance setting in Table 7 also uses knowledge distillation [31], [68].

TABLE 8 Comparison Between NAT Searched Model and Representative Models on ImageNet Classification Under Standard Training Setup, and as Feature Extractors on MS COCO [86] Object Detection Task, PASCAL VOC [87] Instance Segmentation Task and Semantic Segmentation Tasks

| Backbone | | MobileNetV3 [22] | FBNetV2 [32] | NAT-M1 (ours) |
|--------------------------|---|-----------------------------------|----------------------------|--|
| #MAdds | | 219M | 238M | 225M |
| ImageNet Top- | 1 Acc. | 74.7 | 75.2 | 75.7 |
| Object Detection | AP AP s/m/l | 31.8 10.4 / 37.3 / 50.1 | 31.1 10.9 / 36.6 / 48.4 | 32.2 11.5 / 37.9 / 49.7 |
| Instance Segmentation | AP bbox AP mask | 44.0 43.6 | 44.8 43.9 | 45.2 44.3 |
| Semantic Segmentation | Cityscapes [20] PASCAL VOC [87] COCO-Stuff [88] | 73.0 73.8 28.5 | 72.6 73.6 28.5 | 74.0 75.9 29.5 |

TABLE 9 Effect of Different Training Setups

| Training Settings | Random Initialization | | Inherited from Supernet | | |
|-------------------|--------------------------|----------|-------------------------|--------------|--|
| | standard | advanced | w/o fine-tune | w/ fine-tune | |
| NAT-M1 | 75.7 | 77.1 | 75.9 | 77.5 | |
| NAT-M2 | 76.9 | 78.0 | 77.4 | 78.6 | |
| NAT-M3 | 78.2 | 79.1 | 78.9 | 79.9 | |
| NAT-M4 | 78.8 | 79.5 | 79.4 | 80.5 | |

Details of the standard and advanced settings under Random Initialization *are provided in Table 7.*

6 CONCLUSION

This paper considered the problem of designing custom neural network architectures that trade-off multiple objectives for a given image classification task. We introduced Neural Architecture Transfer (NAT), a practical and effective approach for this purpose. We described our efforts to harness the concept of a supernet and an evolutionary search algorithm for designing task-specific neural networks trading-off accuracy and computational complexity. We also showed how to use an online regressor, as a surrogate model to predict the accuracy of subnets in the supernet. Experimental evaluation on eleven benchmark image classification datasets, ranging from large-scale multi-class to small-scale fine-grained tasks, showed that networks obtained by NAT outperform conventional fine-tuning based transfer learning, while being orders of magnitude more efficient under mobile settings (≤600M Multiply-Adds). NAT was especially effective for small-scale fine-grained tasks where fine-tuning pretrained ImageNet models is ineffective. Finally, we also demonstrated the utility of NAT in optimizing up to twelve objectives with a subsequent trade-off analysis procedure for identifying a single preferred solution. Overall, NAT is the first large scale demonstration of many-objective neural architecture search for designing custom task-specific models on diverse image classification datasets.

ACKNOWLEDGMENTS

This work was supported by the National Science Foundation under Cooperative Agreement No. DBI-0939454. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.

REFERENCES

- O. Russakovsky et al., "Imagenet large scale visual recognition [1] challenge," Int. J. Comput. Vis., vol. 115, no. 3, pp. 211–252, 2015. K. Simonyan and A. Zisserman, "Very deep convolutional net-
- [2] works for large-scale image recognition," in Proc. Int. Conf. Learn. Representations, 2015.
- K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recog-*[3] nit., 2016, pp. 770-778.
- A. Krizhevsky, I. Sutskever, and G. E. Hinton, "Imagenet classifi-[4] cation with deep convolutional neural networks," in Proc. Annu. Conf. Neural Inf. Process. Syst., 2012, pp. 1097-1105.
- C. Szegedy et al., "Going deeper with convolutions," in Proc. IEEE [5] Conf. Comput. Vis. Pattern Recognit., 2015, pp. 1-9.
- G. Huang, Z. Liu, L. Van Der Maaten, and K. Q. Weinberger, [6] "Densely connected convolutional networks," in Proc. IEEE Conf. *Comput. Vis. Pattern Recognit.*, 2017, pp. 2261–2269. S. Kornblith, J. Shlens, and Q. V. Le, "Do better imagenet models
- [7] transfer better?," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit., 2019, pp. 2656–2666.
- [8] B. Zoph, V. Vasudevan, J. Shlens, and Q. V. Le, "Learning transferable architectures for scalable image recognition," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit., 2018, pp. 8697-8710.
- [9] A. Krizhevsky et al., "Learning multiple layers of features from tiny images," Citeseer, 2009.
- [10] G. Bender, P.-J. Kindermans, B. Zoph, V. Vasudevan, and Q. Le, "Understanding and simplifying one-shot architecture search," in Proc. 35th Int. Conf. Mach. Learn., 2018, pp. 550-559.
- [11] K. Deb and H. Jain, "An evolutionary many-objective optimization algorithm using reference-point-based nondominated sorting approach, part I: Solving problems with box constraints," IEEE Trans. Evol. Computation, vol. 18, no. 4, pp. 577-601, Aug. 2014.

- [13] A. Coates, A. Ng, and H. Lee, "An analysis of single-layer networks in unsupervised feature learning," in Proc. 14th Int. Conf. Artif. Intell. Statist., 2011, pp. 215-223.
- [14] L. Bossard, M. Guillaumin, and L. Van Gool, "Food-101-mining discriminative components with random forests," in Proc. Eur. Conf. Comput. Vis., 2014, pp. 446-461.
- [15] J. Krause, M. Stark, J. Deng, and L. Fei-Fei, "3D object representations for fine-grained categorization," in *Proc. IEEE Workshop 3D* Representation Recognit., 2013, pp. 554–561.
- [16] S. Maji, J. Kannala, E. Rahtu, M. Blaschko, and A. Vedaldi, "Finegrained visual classification of aircraft," 2013, arXiv:1306.5151.
- M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, and A. Vedaldi, "Describing textures in the wild," in *Proc. IEEE Conf. Comput. Vis.* [17] Pattern Recognit., 2014, pp. 3606-3613.
- [18] O. M. Parkhi, A. Vedaldi, A. Zisserman, and C. Jawahar, "Cats and dogs," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2012, pp. 3498–3505.
- [19] M. Nilsback and A. Zisserman, "Automated flower classification over a large number of classes," in Proc. 6th Indian Conf. Comput. Vis. Graph. Image Process., 2008, pp. 722–729.
- [20] M. Cordts et al., "The cityscapes dataset for semantic urban scene understanding," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2016, pp. 3213–3223.
- [21] C. Liu, L.-C. Chen, F. Schroff, H. Adam, W. Hua, A. L. Yuille, and L. Fei-Fei, "Auto-deeplab: Hierarchical neural architecture search for semantic image segmentation," in Proc. IEEE Conf. Comput. *Vis. Pattern Recognit.*, 2019, pp. 82–92. A. Howard *et al.*, "Searching for mobilenetv3," in *Proc. IEEE/CVF*
- [22] Int. Conf. Comput. Vis., 2019, pp. 1314-1324.
- [23] C. Liu et al., "Progressive neural architecture search," in Proc. Eur. Conf. Comput. Vis., 2018, pp. 19–35. [24] H. Liu, K. Simonyan, and Y. Yang, "DARTS: Differentiable archi-
- tecture search," in Proc. Int. Conf. Learn. Representations, 2019.
- [25] T. Elsken, J. H. Metzen, and F. Hutter, "Efficient multi-objective neural architecture search via lamarckian evolution," in Proc. Int. Conf. Learn. Representations, 2019.
- [26] H. Cai, L. Zhu, and S. Han, "ProxylessNAS: Direct neural architecture search on target task and hardware," in Proc. Int. Conf. Learn. Representations, 2019.
- [27] M. Tan *et al.*, "Mnasnet: Platform-aware neural architecture search for mobile," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2019, pp. 2815-2823.
- [28] M. Tan and Q. V. Le, "Efficientnet: Rethinking model scaling for convolutional neural networks," in Proc. Int. Conf. Mach. Learn., 2019, pp. 6105-6114.
- [29] X. Dai et al., "Chamnet: Towards efficient network design through platform-aware model adaptation," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2019, pp. 11390–11399.
- [30] Z. Guo et al., "Single path one-shot neural architecture search with uniform sampling," in Proc. Eur. Conf. Comput. Vis., 2020, pp. 544-560.
- [31] H. Cai, C. Gan, T. Wang, Z. Zhang, and S. Han, "Once for all: Train one network and specialize it for efficient deployment," in Proc. Int. Conf. Learn. Representations, 2020.[32] A. Wan et al., "Fbnetv2: Differentiable neural architecture search
- for spatial and channel dimensions," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2020, pp. 12962–12971.
- X. Yao, "Evolving artificial neural networks," Proc. IEEE, vol. 87, [33] no. 9, pp. 1423-1447, Sep. 1999.
- [34] K. O. Stanley and R. Miikkulainen, "Evolving neural networks through augmenting topologies," Evol. Computation, vol. 10, no. 2, pp. 99-127, 2002.
- [35] B. Zoph and Q. V. Le, "Neural architecture search with reinforcement learning," in Proc. Int. Conf. Learn. Representations, 2017.
- [36] Z. Zhong, J. Yan, W. Wu, J. Shao, and C. Liu, "Practical block-wise neural network architecture generation," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2018, pp. 2423-2432.
- [37] H. Liu, K. Simonyan, O. Vinyals, C. Fernando, and K. Kavukcuo-"Hierarchical representations for efficient architecture glu, search," in Proc. Int. Conf. Learn. Representations, 2018.
- [38] E. Real, A. Aggarwal, Y. Huang, and Q. V. Le, "Regularized evolution for image classifier architecture search," in Proc. AAAI Conf. Artif. Intell., 2019, pp. 4780–4789.
- [39] D. Lian et al., "Towards fast adaptation of neural architectures with meta learning," in Proc. Int. Conf. Learn. Representations, 2020.

- [40] T. Elsken, B. Staffler, J. H. Metzen, and F. Hutter, "Meta-learning of neural architectures for few-shot learning," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2020, pp. 12362–12372.
- [41] M. Wistuba, "XferNAS: Transfer neural architecture search," 2019, arXiv: 1907.08307.
- [42] J. Fang *et al.*, "EAT-NAS: Elastic architecture transfer for accelerating large-scale neural architecture search," 2019, *arXiv*: 1901.05884.
- [43] C. Wong, N. Houlsby, Y. Lu, and A. Gesmundo, "Transfer learning with neural autoML," in *Proc. 32nd Int. Conf. Neural Inf. Pro*cess. Syst., 2018, pp. 8366–8375.
- [44] E. Kokiopoulou, A. Hauth, L. Sbaiz, A. Gesmundo, G. Bartok, and J. Berent, "Fast task-aware architecture inference," 2019, arXiv: 1902.05781.
- [45] B. Baker, O. Gupta, R. Raskar, and N. Naik, "Accelerating neural architecture search using performance prediction," 2017, arXiv: 1705.10823.
- [46] H. Pham, M. Guan, B. Zoph, Q. Le, and J. Dean, "Efficient neural architecture search via parameters sharing," in *Proc. 35th Int. Conf. Mach. Learn.*, 2018, pp. 4095–4104.
- [47] L. Li and A. Talwałkar, "Random search and reproducibility for neural architecture search," 2019, arXiv: 1902.07638.
- [48] S. Xie, A. Kirillov, R. Girshick, and K. He, "Exploring randomly wired neural networks for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2019, pp. 1284–1293.
- *Comput. Vis. Pattern Recognit.*, 2019, pp. 1284–1293.
 [49] K. Yu, C. Sciuto, M. Jaggi, C. Musat, and M. Salzmann, "Evaluating the search phase of neural architecture search," in *Proc. Int. Conf. Learn. Representations*, 2020.
- [50] A. Brock, T. Lim, J. Ritchie, and N. Weston, "SMASH: One-shot model architecture search through hypernetworks," in *Proc. Int. Conf. Learn. Representations*, 2018.
- [51] Z. Lu et al., "NSGA-Net: Neural architecture search using multiobjective genetic algorithm," in Proc. Genetic Evol. Computation Conf., 2019, pp. 419–427.
- [52] J.-D. Dong, A.-C. Cheng, D.-C. Juan, W. Wei, and M. Sun, "DPPnet: Device-aware progressive search for pareto-optimal neural architectures," in *Proc. Eur. Conf. Comput. Vis.*, 2018, pp. 540–555.
- [53] X. Chu, B. Zhang, R. Xu, and J. Li, "Fairnas: Rethinking evaluation fairness of weight sharing neural architecture search," 2019, arXiv: 1907.01845.
- [54] Z. Lu, K. Deb, and V. N. Boddeti, "MUXConv: Information multiplexing in convolutional neural networks," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2020, pp. 12041–12050.
- [55] J. Bracken and J. T. McGill, "Mathematical programs with optimization problems in the constraints," *Operations Res.*, vol. 21, no. 1, pp. 37–44, 1973. [Online]. Available: http://www.jstor.org/stable/169087
- [56] M. Sandler, A. Howard, M. Zhu, A. Zhmoginov, and L.-C. Chen, "MobilenetV2: Inverted residuals and linear bottlenecks," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2018, pp. 4510–4520.
- [57] A. G. Howard *et al.*, "Mobilenets: Efficient convolutional neural networks for mobile vision applications," 2017, arXiv: 1704.04861.
- [58] Y. Sun, H. Wang, B. Xue, Y. Jin, G. G. Yen, and M. Zhang, "Surrogate-assisted evolutionary deep learning using an end-toend random forest-based performance predictor," *IEEE Trans. Evol. Computation*, vol. 24, no. 2, pp. 350–364, Apr. 2020.
- [59] E. Real et al., "Large-scale evolution of image classifiers," in Proc. 34th Int. Conf. Mach. Learn., 2017, pp. 2902–2911.
- [60] K. Deb and R. B. Agrawal, "Simulated binary crossover for continuous search space," Complex Syst., vol. 9, no. 2, pp. 115–148, 1995.
- [61] I. Das and J. E. Dennis, "Normal-boundary intersection: A new method for generating the pareto surface in nonlinear multicriteria optimization problems," *SIAM J. Optim.*, vol. 8, no. 3, pp. 631– 657, Mar. 1998. [Online]. Available: https://doi.org/10.1137/ S1052623496307510
- [62] B. Wu et al., "FBNet: Hardware-aware efficient convnet design via differentiable neural architecture search," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2019, pp. 10726–10734.
- [63] E. D. Cubuk, B. Zoph, J. Shlens, and Q. V. Le, "Randaugment: Practical automated data augmentation with a reduced search space," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.* Workshops, 2020, pp. 3008–3017.
- [64] J. Mei et al., "Atomnas: Fine-grained end-to-end neural architecture search," in Proc. Int. Conf. Learn. Representations, 2020.
- [65] Y. Li et al., "Neural architecture search for lightweight nonlocal networks," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2020, pp. 10297–10306.

- [66] C. Li *et al.*, "Blockwisely supervised neural architecture search with knowledge distillation," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2020, pp. 1986–1995.
 [67] M. Tan and Q. V. Le, "Mixconv: Mixed depthwise convolutional
- [67] M. Tan and Q. V. Le, "Mixconv: Mixed depthwise convolutional kernels," in *Proc. British Mach. Vis. Conf.*, 2019, p. 74.
- [68] J. Yu et al., "BigNAS: Scaling up neural architecture search with big single-stage models," in Proc. Eur. Conf. Comput. Vis., 2020, pp. 702–717.
- [69] C. Szegedy, S. Ioffe, V. Vanhoucke, and A. A. Alemi, "Inceptionv4, inception-resnet and the impact of residual connections on learning," in *Proc. 31st AAAI Conf. Artif. Intell.*, 2017, pp. 4278– 4284.
- [70] X. Wang, D. Kihara, J. Luo, and G.-J. Qi, "Enaet: Self-trained ensemble autoencoding transformations for semi-supervised learning," 2019, arXiv: 1911.09265.
- [71] N. Nayman, A. Noy, T. Ridnik, I. Friedman, R. Jin, and L. Zelnik, "XNAS: Neural architecture search with expert advice," in *Proc. Advances Neural Inf. Process. Syst.*, 2019, pp. 1977–1987.
- [72] L.-C. Chen, G. Papandreou, I. Kokkinos, K. Murphy, and A. L. Yuille, "Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected CRFs," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 40, no. 4, pp. 834–848, Apr. 2018.
- [73] A. Newell, K. Yang, and J. Deng, "Stacked hourglass networks for human pose estimation," in *Proc. Eur. Conf. Comput. Vis.*, 2016, pp. 483–499.
- [74] T.-Y. Lin, P. Dollár, R. Girshick, K. He, B. Hariharan, and S. Belongie, "Feature pyramid networks for object detection," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2017, pp. 936–944.
- pp. 936–944.
 [75] C. Yu, J. Wang, C. Peng, C. Gao, G. Yu, and N. Sang, "BiSeNet: Bilateral segmentation network for real-time semantic segmentation," in *Proc. Eur. Conf. Comput. Vis.*, 2018, pp. 334–349.
- [76] H. Zhao, J. Shi, X. Qi, X. Wang, and J. Jia, "Pyramid scene parsing network," in Proc. IEEE Conf. Comput. Vis. Pattern Recognit., 2017, pp. 6230–6239.
- [77] L.-C. Chen, Y. Zhu, G. Papandreou, F. Schroff, and H. Adam, "Encoder-decoder with atrous separable convolution for semantic image segmentation," in *Proc. Eur. Conf. Comput. Vis.*, 2018, pp. 833–851.
- [78] É. Zitzler and L. Thiele, "Multiobjective optimization using evolutionary algorithms — a comparative case study," in *Parallel Problem Solving From Nature* — *PPSN V*, A. E. Eiben, T. Bäck, M. Schoenauer, and H.-P. Schwefel, Eds. Berlin, Germany: Springer, 1998, pp. 292–301.
- [79] F. Hutter, H. H. Hoos, and K. Leyton-Brown, "Sequential modelbased optimization for general algorithm configuration," in *Proc. Int. Conf. Learn. Intell. Optim.*, 2011, pp. 507–523.
- [80] P. Goyal et al. "Accurate, large minibatch SGD: Training imagenet in 1 hour," 2017, arXiv: 1706.02677.
- [81] E. D. Cubuk, B. Zoph, J. Shlens, and Q. V. Le, "Randaugment: Practical automated data augmentation with a reduced search space," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. Workshops*, 2020, pp. 3008–3017.
- [82] Z. Zhong, L. Zheng, G. Kang, S. Li, and Y. Yang, "Random erasing data augmentation," in *Proc. AAAI Conf. Artif. Intell.*, 2020, pp. 13001–13008.
- [83] G. Huang, Y. Sun, Z. Liu, D. Sedra, and K. Q. Weinberger, "Deep networks with stochastic depth," in *Proc. Eur. Conf. Comput. Vis.*, 2016, pp. 646–661.
- [84] M. Tan, R. Pang, and Q. V. Le, "Efficientdet: Scalable and efficient object detection," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2020, pp. 10778–10787.
- [85] D. Bolya, C. Zhou, F. Xiao, and Y. J. Lee, "YOLACT: Real-time instance segmentation," in *Proc. IEEE/CVF Int. Conf. Comput. Vis.*, 2019, pp. 9156–9165.
- [86] T.-Y. Lin et al., "Microsoft COCO: Common objects in context," in Proc. Eur. Conf. Comput. Vis., 2014, pp. 740–755.
- [87] M. Everingham, S. A. Eslami, L. Van Gool, C. K. Williams, J. Winn, and A. Zisserman, "The pascal visual object classes challenge: A retrospective," *Int. J. Comput. Vis.*, vol. 111, no. 1, pp. 98–136, 2015.
- [88] H. Caesar, J. Uijlings, and V. Ferrari, "COCO-stuff: Thing and stuff classes in context," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, 2018, pp. 1209–1218.



Zhichao Lu (Student Member, IEEE) received the BSc and PhD degrees in electrical and computer engineering from Michigan State University, East Lansing, in 2013 and 2020, respectively. He is currently a postdoc research fellow with the Department of Computer Science and Engineering, Southern University of Science and Technology, Shenzhen, China. His research interests include the field of evolutionary machine learning, notably machine learning assisted evolutionary algorithms, automated machine learning, and in particular evo-

lutionary neural architecture search. He received the Best Paper Award at GECCO 2019 under evolutionary machine learning track.



Computation (SIGEVO), 2005.

Gautam Sreekumar received the BTech degree in electrical engineering from the Indian Institute of Technology Madras. He is currently working toward the PhD degree at the Department of Computer Science and Engineering, Michigan State University. His research interests include the field of deep neural networks, particularly evolutionary neural architecture search for vision tasks.

Erik Goodman is currently the PI and executive

director of the BEACON Center for the Study of

Evolution in Action, an NSF Science and Technol-

ogy Center headquartered at Michigan State Uni-

versity, funded at \$47.5 million for 2010-20. He

received the PhD degree, Computer and Communication Sciences, University of Michigan, 1972. Assistant professor-full professor. Michigan

State University, 1971-, Electrical and Computer

Engineering, Mechanical Engineering, Computer

Science and Engineering. Director, Case Center

for Computer-Aided Engineering and Manufacturing, 1983-2002; Direc-

tor. Co-founder and VP Technology, Red Cedar Technology, Inc., which

develops design optimization software, now owned by Siemens. Chair

and Senior Fellow, International Society for Genetic and Evolutionary

Computation; Founding Chair, ACM SIG on Genetic and Evolutionary



Wolfgang Banzhaf is currently the John R. Koza chair for Genetic Programming and a professor at the Department of Computer Science and Engineering, Michigan State University. His research interests include the field of bioinspired computing, notably evolutionary computation and complex adaptive system, and in particular genetic programming. He is founding editor-in-chief of the Springer journal *Genetic Programming and Evolving Machines*, senior fellow, International Society for Genetic and Evolu-

tionary Computation, and won the EvoStar Award for sustained contributions to the field of Evolutionary Computation in Europe.



Kalyanmoy Deb (Fellow, IEEE) received the bachelor's degree in mechanical engineering from IIT Kharagpur, in India, and the master's and PhD degrees from the University of Alabama, Tuscaloosa, in 1989 and 1991, respectively. He is the Koenig Endowed chair professor with the Department of Electrical and Computer Engineering, Michigan State University, East Lansing, Michigan. He is largely known for his seminal research in evolutionary multi-criterion optimization. He has published more than 544 interna-

tional journal and conference research papers. His current research interests include evolutionary optimization and its application in design, modeling, AI, and machine learning. He is a recipient of the IEEE CIS EC Pioneer Award in 2018, the Lifetime Achievement Award from Clarivate Analytics in 2017, the Infosys Prize in 2012, and the Edgeworth-Pareto Award in 2008. He is a fellow ASME. For more information, please visit http://www.coin-lab.org



Vishnu Naresh Boddeti (Member, IEEE) received the PhD degree in electrical and computer engineering program from Carnegie Mellon University, in 2013. He is currently an assistant professor at the Computer Science Department, Michigan State University. His research interests include computer vision, pattern recognition and machine learning. He received the Best Paper Award at BTAS 2013, the Best Student Paper Award at GECCO 2019.

▷ For more information on this or any other computing topic, please visit our Digital Library at www.computer.org/csdl.